



Kelly Young  
Dirigo Software, LLC  
PO Box 53  
Readfield, ME 04355  
dirigosoftware.com  
dsw@dirigosoftware.com

---

## CANADIAN VEHICLE SPECIFICATIONS REPORT

Model Year: **2013** 8/18/2018  
Make: **AUDI**  
Model: **A4 4DR SEDAN 2.0 TFSI QUATTRO/PREMIUM/PREMIUM**

---

### Imperial (weights in pounds and distances in inches):

Curb Weight:	<b>3616.2</b>	The operational weight of the vehicle without driver, passengers or cargo.
Wheelbase:	<b>110.6</b>	The distance from the center of the front axle to center of rear axle.
Track Width (Front):	<b>61.0</b>	The lateral distance between the center of the front wheels.
Track Width (Rear):	<b>60.6</b>	The lateral distance between the center of the rear wheels.
Overall Length:	<b>185.0</b>	The distance from the front to the rear (not including bumpers on pickup trucks).
Overall Width:	<b>72.0</b>	The measurement at the widest part of the vehicle (excluding mirrors).
Overall Height:	<b>56.3</b>	The distance from ground to highest point on vehicle (excluding antennas, roof racks).
Wt Dist (Frt/Rear):	<b>55/45</b>	The % of operational weight on the front and rear axles.
A1:	<b>48.8</b>	Distance between the front bumper and the base of the windshield.
B1:	<b>19.7</b>	See below
C1:	<b>14.2</b>	The maximum vertical height of the side glass.
D1:	<b>31.1</b>	The vertical distance between base of side glass and lower edge of rocker panel.
E1:	<b>41.7</b>	The distance between the side rails OR maximum width of top.
F1:	<b>34.6</b>	The front overhang.
G1:	<b>40.6</b>	The rear overhang.

The value of B1 depends on the vehicle:

Passenger car: Longitudinal distance between the center of the rear bumper and center of the base of the backlight.  
Station wagons and Vans: Longitudinal distance between the backlight top moulding and the front door latch pillar.  
Pick-ups: Longitudinal distance between the rearmost projection and the front door latch pillar.